

Electro Optical Components, Inc.

5460 Skylane Boulevard, Santa Rosa, CA 95403 Toll Free: 855-EOC-6300

www.eoc-inc.com | info@eoc-inc.com



ilumCURE - UV light source

(Article no. 1600000041)

The UV handheld lighting device ilumCURE by IMM Photonics is an UV light source with a central wavelength of 365 nm. It serves as mobile UV light source for the cureing of UV adhesives.

The ilumCURE features a robust aluminium casing and was especially developed for fieldwork. The integrated lithium ion accumulator allows 3.5 hours of continuous operation. Thanks to the high-performance UV LED, the cureing of UV adhesives requires only a few seconds of exposure.



The ilumCURE can be re-charged via a laptop / PC or on the move via a USB port in the car.

Technical specifications Hand-held UV Exposure Unit (Article no. 1600000041)

| Overall Dimensions | Length=185 mm, max. diameter 27.5 mm |
|---|--|
| Dimensions of Application nozzle | Nozzle length 53 mm Diameter 5 mm (applies for 8 mm in length) |
| Weight / Material | Ca. 100 g / Full metal housing, anodised aluminium |
| Wavelength | 365 nm |
| Output | 200 mW |
| System start-up | Via buttons on housing |
| Power supply / Connection | USB- and /or battery operation / USB-B (5 V, 500 mA) |
| Battery | Li-ION / 3.6 V, 2250 mAh |
| Battery safety functions | Overvoltage and undervoltage, overcurrent, overtemperature |
| Charging time for completely discharged battery | 5.5 hours |
| Operating time with fully charged battery | 3.5 hours |
| Battery indicator (next to USB-B jack) | Red / Green: Pre-charging for nearly completely discharged battery Red: Charging in progress Green: Battery is fully charged |
| Operating and storage temperature | +5 °C to + 45°C / -10 °C to + 70°C |
| Humidity | 5 % to 95 % r. h. (non-condensing) |
| Delivery | ilumCURE Quadrosafe (L=120 mm - 200 mm, D=45 mm, PP, transparent) Cable USB-A to USB-B Instruction manual |
| Subject to technical modifications. As per August 201 | 2 @ IMM Photonics Cmb H |