



# Electro Optical Components, Inc.

5460 Skylane Boulevard, Santa Rosa, CA 95403


Toll Free: 855-EOC-6300

[www.eoc-inc.com](http://www.eoc-inc.com) | [info@eoc-inc.com](mailto:info@eoc-inc.com)



## BTX Series- customised bench supply

200 to 250Vdc 100nA



Reference: **BTX-P250-100n**



This picture is not exactly representative.

Parameters	Specifications
Enclosure	Iron case with front and rear panels in aluminum
Dimensions	L 200 x W 140 x H 90 mm
Front panel	<p>Voltage and current adjustments (two potentiometers)</p> <ul style="list-style-type: none"> <li>➤ Voltage from 200 to 250Vdc</li> <li>➤ Current from 0 to 100nA</li> </ul> <p>Constant voltage and current operation mode ( automatic conversion)</p> <p>Voltage and current display: resolution 1V and 0.1nA</p> <p>ON/OFF switch</p>
Output	<p>Positive output with respect to earth.</p> <p>Ripple &lt;10mVp-p</p>
Output connector	SMA
Indicators	<p>Two LED showing:</p> <ul style="list-style-type: none"> <li>• ON State</li> <li>• Current mode operation (overload condition)</li> </ul>
Rear panel	<p>Universal 87-264Vac inlet</p> <p>Output connector</p>
Operating temperature	10°C to 50°C

This High Voltage power supply satisfies the requirements of EC Directives Safety.

All specifications are subject to change without notice.

Non contractual document

